

ABSTRACT OF DISCLOSURE

Sub B34 → In a dynamo electric machine provided with a stator and a permanent magnet type rotor 2, on or near
 5 circumferential surface of the rotor 2 facing the stator 1 p·n pieces of permanent magnet blocks 21 are disposed, herein p is number of poles of the rotor and n is an integer equal to or more than 2, and each of the permanent magnet blocks satisfies the following
 10 condition (1);

$$(\theta_i) - (\theta_{i+1}) = (A_i \cdot p / 2) \quad \dots (1)$$

Wherein, when assuming that clockwise direction is plus, A_i is an angle formed between radial center lines of i th permanent magnet block and $(i+1)$ th
 15 permanent magnet block, θ_i is an angle formed between magnetization direction of the i th permanent magnet block and the outward radial direction thereof, and θ_{i+1} is an angle formed between magnetization direction of the $(i+1)$ th permanent magnet block and
 20 the outward radial direction thereof, and further, when assuming that stator 1 includes m pieces of salient poles disposed with an equal interval the dynamo electric machine satisfies the following condition (2);

Sub B35 → $m/p \leq 1.5 \quad \dots (2),$

thereby, a permanent magnet type dynamo electric machine with reduced size, increased efficiency and

10066735-020602

decreased cogging torque can be realized.

10066735.020602